




### Bussola di riduzione PP

Estremità maschio filettata (1° R di riferimento)  
 estremità femmina filettata (R<sub>1</sub> ridotto)  
 Codice: DDFM

### PP reducing bush

Male parallel threaded (1<sup>st</sup> R of reference)  
 socket parallel threaded (R<sub>1</sub> reduced)  
 Code: DDFM



G <sub>1</sub> x G (inch)	L (mm)	L <sub>1</sub> (mm)	H (mm)	E (mm)	K (mm)
3/8" x 1/4"	10,0	10,0	20,0	20,0	17,0
1/2" x 3/8"	16,0	15,0	26,5	28,0	25,0
3/4" x 3/8"	18,0	14,0	33,0	30,5	27,0
3/4" x 1/2"	18,0	17,0	33,0	31,0	27,0
1" x 1/2"	19,5	17,0	35,0	41,0	36,0
1" x 3/4"	19,5	19,0	35,0	41,0	36,0
1 1/4" x 1/2"	21,0	15,0	39,0	49,5	46,0
1 1/4" x 3/4"	21,0	16,0	39,0	49,5	46,0
1 1/4" x 1"	21,0	19,0	39,0	49,5	46,0
1 1/2" x 3/4"	21,0	16,0	39,0	54,0	50,0
1 1/2" x 1"	21,0	21,0	39,0	54,0	50,0
1 1/2" x 1 1/4"	21,0	29,0	39,0	54,0	50,0
2" x 1"	25,5	19,0	43,5	69,0	65,0
2" x 1 1/4"	25,5	21,0	43,5	69,0	65,0
2" x 1 1/2"	25,5	21,0	43,5	69,0	65,0

- Colore: Beige RAL 7032
- Giunzione: Filettatura cilindrica secondo UNI ISO 228/1
- Dimensioni: Ø 1/4" ÷ Ø 2"
- Temperature di esercizio: - 10°C ÷ +100 °C
- Pressione di esercizio max: 10 bar

- Color: Beige RAL 7032
- Joint: Gas parallel threading standards UNI ISO 228/1
- Dimensions: Ø 1/4" ÷ Ø 2"
- Working temperature: - 10°C ÷ +100 °C
- Max working pressure: 10 bar