




**Gomito 45° PE100**

Estremità femmina per saldatura nel bicchiere

**PE100 elbow 45°**

Female sockets fusion



<b>d (mm)</b>	<b>D (mm)</b>	<b>k (mm)</b>	<b>t (mm)</b>	<b>Peso Wiegth (kg)</b>	<b>PN (bar)</b>
20	30,0 ± 1,0	11,0 ± 1,0	16,0 ± 1,0	0,02	16
25	34,5 ± 1,0	14,0 ± 1,0	18,0 ± 1,0	0,02	16
32	43,5 ± 1,0	17,0 ± 1,0	20,0 ± 1,0	0,04	16
40	53,0 ± 1,0	21,0 ± 1,0	21,5 ± 1,0	0,06	16
50	64,8 ± 1,0	26,0 ± 1,0	24,6 ± 1,0	0,09	16
63	80,9 ± 1,0	33,0 ± 1,0	28,6 ± 1,0	0,17	16
75	92,0 ± 1,0	38,5 ± 1,0	32,5 ± 1,0	0,22	16
90	113,7 ± 1,0	46,0 ± 1,0	36,5 ± 1,0	0,41	16
110	135,0 ± 1,0	56,0 ± 1,0	42,7 ± 1,0	0,59	16

Materiale: PE 100

Colore: nero

Idoneo per linee chimiche, acqua e gas

*Material: PE 100*

*Colour: black*

*Suitable for chemical, water and gas piping system*